


SPECIFICATIONS - 1" DEFLECTION SPRING HANGER WITH NEOPRENE ELEMENT AND SPRING NEOPRENE CUP

Model	Rated Load		Rated Deflection		Spring Color		Approx. WT.	
	lbs.	KN	in	mm	outer	inner	lbs.	Kg
IHACE-30	30	0.134	1.0	25.4	YELLOW		1.55	0.71
IHACE-50	50	0.223	1.0	25.4	GREEN		1.55	0.71
IHACE-100	100	0.445	1.0	25.4	BLACK		1.65	0.75
IHACE-150	150	0.668	1.0	25.4	RED		1.65	0.75
IHACE-200	200	0.89	1.0	25.4	BLUE		1.80	0.82
IHACE-300	300	1.335	1.0	25.4	WHITE		1.85	0.84
IHACE-400	400	1.78	1.0	25.4	BROWN		2.00	0.91
IHACE-500	500	2.225	1.0	25.4	ORANGE		2.05	0.93
IHACE-600	600	2.669	1.0	25.4	GREY		2.15	0.98

HARDWARE NOT INCLUDED - SPRING CUP: ZINC PLATED



Model					
IHACE-30-600					
H		W		L	
in	mm	in	mm	in	mm
5 1/2	140	2 3/8	67	2 1/2	64

Notes:

- Housing is designed to allow 30° misalignment for hanger rod
- Neoprene Element is designed to provide up to 0.35" deflection at rated load
- Springs are powder – coated for maximum corrosion protection, and are designed to have minimum 50% over travel under rated load

PROJECT INFORMATION		EQUIPMENT INFORMATION		Canada location	USA Location	
Customer:		Type:		35 Silton Road Woodbridge ON L4L 7Z8 CANADA T: 905-856-5001	7700 Irvine Centre Drive Suite 800 Irvine, CA, 92618 U.S.A T: 949-788-2930	
Project:		Qty Required:				
Drawing No:		Operating Weight:				
Notes:				www.isotechindustries.com		