

IHBE-3P ISOTECH PRE-COMPRESSED SPRING HANGER IN-LINE WITH NEOPRENE ELEMENT

File No. : ISOCS-IHBE-3P-30-1500

Date: 09/15/15

ISOIN-IHBE-3P-30-1500, Installation Instructions Document, to be Reviewed for Installation

SPECIFICATIONS : IHBE-3" DEFLECTION ISOTECH PRE-COMPRESSED SPRING HANGER IN-LINE WITH NEOPRENE ELEMENT

Model	RATED LOAD		RATED DEFLECTION		THREADED ROD / COUPLING NUT SIZE Ø(in)	SPRING COLOR	NEOPRENE ELEMENT COLOR	APPROX. WT.	
	Lbf.	Kn	in	mm				Lbs.	Kg
IHBE-3P-30	30	0.133	3	76.2	3/8	PINK	RED	5.50	2.50
IHBE-3P-50	50	0.222	3	76.2	3/8	PURPLE	RED	5.50	2.50
IHBE-3P-100	100	0.445	3	76.2	3/8	BROWN	RED	5.61	2.55
IHBE-3P-200	200	0.89	3	76.2	3/8	BLACK	RED	5.79	2.63
IHBE-3P-300	300	1.335	3	76.2	3/8	WHITE	BLUE	5.96	2.71
IHBE-3P-400	400	1.779	3	76.2	1/2	GREEN	BLUE	6.14	2.79
IHBE-3P-500	500	2.225	3	76.2	1/2	YELLOW	BLACK	6.31	2.87
IHBE-3P-600	600	2.669	3	76.2	5/8	ORANGE	BLACK	6.49	2.95
IHBE-3P-800	800	3.559	3	76.2	5/8	GREY	GREEN	6.67	3.03
IHBE-3P-1000	1000	4.449	3	76.2	5/8	RED	YELLOW	6.84	3.11
IHBE-3P-1500	1500	6.773	3	76.2	3/4	BLUE	YELLOW	7.02	3.19



HARDWARE NOT INCLUDED - SPRING CUP: ZINC PLATED

Dimension : IHBE-3" DEFLECTION ISOTECH PRE-COMPRESSED SPRING HANGER IN-LINE WITH NEOPRENE ELEMENT

Model	H		W		L	
	in	mm	in	mm	in	mm
IHBE-3P-30-1500	8 1/2	216	4 1/4	108	4 3/8	112


ISOLATOR'S LOCATIONS

1:	5:
2:	6:
3:	7:
4:	8:



Notes:

- Housing is powder – coated and designed to allow 30° misalignment for hanger rod
- Neoprene Element is designed to provide up to 0.35" deflection at rated load
- Springs are powder – coated for maximum corrosion protection, and are designed to have minimum 50% over travel

PROJECT INFORMATION		EQUIPMENT INFORMATION		<div>Canada location</div> <div>35 Silton Road Woodbridge ON L4L 7Z8 CANADA T: 905-856-5001</div> <div>USA Location</div> <div>3021 E Coronado St. Anaheim, CA.,92806 U.S.A T: 949-788-2930</div> <div>Tool free : 1-888-831-3311 www.isotechindustries.com</div> <div></div>
Customer:		Type:		
Project:		Qty Required:		
Drawing No:		Operating Weight:		
Notes:				

