

IRBH-1 ISOTECH RISER BRANCH SPRING HANGER

File No.: ISCOS-IRBH-1-60-1200



Date:12/15/17

ISOIN-IRBH-1-60-1200, Installation Instructions Document, to be Reviewed for Installation

SPECIFICATIONS : IRBH-1" DEFLECTION ISOTECH RISER BRANCH SPRING HANGER

Model	Rated Load		Rated Deflection		Spring Color (2 Springs)	Approx. WT.	
	lbf.	kN	in	mm		lbs.	kg
IRBH-1-60	60	0.267	1.0	25.4	YELLOW	2.08	0.95
IRBH-1-100	100	0.445	1.0	25.4	GREEN	2.20	1
IRBH-1-200	200	0.89	1.0	25.4	BLACK	2.68	1.22
IRBH-1-300	300	1.335	1.0	25.4	RED	2.70	1.23
IRBH-1-400	400	1.78	1.0	25.4	BLUE	2.90	1.32
IRBH-1-600	600	2.669	1.0	25.4	WHITE	2.95	1.34
IRBH-1-800	800	3.559	1.0	25.4	BROWN	3.20	1.46
IRBH-1-1000	1000	4.449	1.0	25.4	ORANGE	3.50	1.59
IRBH-1-1200	1200	5.338	1.0	25.4	GREY	3.65	1.66


Hardware not included - Spring Cup: Zinc Supplied



Notes:

- Spring(s) are powder - coated to provide maximum corrosion resistance , and are color - coded for easy identification at site - see table for more information
- All springs have additional travel to solid equal to 50% of the Rated Deflection with minimum Kx/Ky ratio of 0.9 - All Elements are safe at solid load

PROJECT INFORMATION		EQUIPMENT INFORMATION		Canada location	USA Location
Customer:		Type:		35 Silton Road Woodbridge ON L4L 7Z8 CANADA T: 905-856-5001	3021 E Coronado St. Anaheim, CA.,92806 U.S.A T: 949-788-2930
Project:		Qty Required:			
Drawing No:		Operating Weight:			
Notes:					



Tool free : 1-888-831-3311
www.isotechindustries.com

COPYRIGHT: UNLESS OTHERWISE AGREED OR STATED IN WRITING, ALL INFORMATION AND DESIGNS DISPLAYED WITHIN ARE ALL THE PROPERTY OF ISOTECH INDUSTRIES INC. AND MAY NOT BE DUPLICATED OR DISTRIBUTED OUTSIDE OF ISOTECH INDUSTRIES INC. WITH THE EXCEPTION OF AUTHORIZED PERSONS WITH LEGITIMATE NEED TO KNOW WHO BY THE USE OF THIS RECOGNIZE ISOTECH INDUSTRIES INC. OWNERSHIP AND WILL COMPLY TO MAINTAIN THIS INFORMATION AND DESIGN IN STRICT CONFIDENCE.